

## LSA PROFIL® Disconnection Module



### Features

- Based on genuine KRONE® LSA-PLUS® connection technology
- Fits on all LSA-PLUS back mount frames, as well as on PROFIL frames
- Suitable for use in all xDSL and ADSL 2+ circuits
- Flexible indoor and outdoor use
- Robust long-term environmental stability
- Supports all LSA-PLUS Series 2 accessories
  - Overvoltage protection
  - Labels
  - Test and connection cords

**Ordering Information**

Description	Catalogue number
LSA PROFIL 10-pair disconnection module Colour: White	6089 1 121-02

**Specifications****Electrical values**

Insulation resistance: >50 GΩ @ 500 V  
 Contact resistance: 1 mΩ

**Safety classification (EN 60950)**

Transient voltage: 2.5k V  
 Operation voltage for basic insulation: 210VDC TNV  
 Pollution severity: II  
 Current-carrying capacity: 2 A  
 Impulse current: 5 kA (8/2μs)

**Conductor diameter/outer diameter of connectable wires**

Single solid wire per contact: 0.35mm/0.68mm to 0.9mm/1.5mm  
 AWG 26 to AWG 20  
 Stranded wires (7 tin-coated copper strands): 0.12mm to 0.32mm/up to 2.1mm (depending on insulation type)  
 AWG 28 to AWG 20

**Overall diameter of connectable wires** (solid insulation) 0.68mm to 1.6mm

**Properties**

Connection frequency: 200 times  
 Plug-in cycles: 250

**Temperature**

Storage (EN 60721-3-1): 1K5 (-40° C to +90° C)/1Z1/1B1/1C1/1S1/1M2  
 Transport (EN 60721-3-2): 2K2 (-40° C to +90° C)/2B1/2C1/2S1/2M2  
 Operation (EN 60721-3-3): 3K5 (-5° C to +60° C)/3Z1/3B1/3C1/3S1/3M2

**Relative humidity:** 95%; no water condensation, no ice**Materials**

Plastics: PBT; resistant against aggressive chemicals (PVC-softener)  
 Plastics flammability class: UL94V-0  
 Halogen free according to: RoHS, European Directive 2002/96/EG  
 Contact: Special brass, silver-plated



KRONE

**Internet:** [www.adckrone.com](http://www.adckrone.com)

For a listing of our global sales office locations, please refer to our web site.

ADC GmbH, Beeskowdamm, 3-11, 14167 Berlin, Germany  
 Phone: +49 30 8453-0 Fax: +49 30 8453-1703

Specifications published here are current as of the date of publication of this document. Because we are continuously improving our products, ADC KRONE reserves the right to change specifications without prior notice. At any time, you may verify product specifications by contacting our world headquarters office in Minneapolis. ADC Telecommunications, Inc. views its patent portfolio as an important corporate asset and vigorously enforces its patents.

101260EN 8/05 Original © 2005 ADC Telecommunications, Inc. All Rights Reserved